

1 X 19 Stainless Steel Wire - Standing Rigging



1 X 19

| Part Number | Nominal Diameter | | Minimum Breaking Load | | Approximate Weight | | Stretch | |
|-------------|------------------|--------|-----------------------|--------|--------------------|----------|--------------|--------------|
| | mm | in | kg | lb | kg/100m | lb/100ft | mm/mm/1000kg | in/in/1000lb |
| S19-M02 | 2 | | 320 | 705 | 1.95 | 1.31 | 0.028961 | 0.0131642 |
| S19-M025 | 2.5 | 3/32 | 500 | 1100 | 3.05 | 2.05 | 0.018535 | 0.0084251 |
| S19-M03 | 3 | | 720 | 1590 | 4.49 | 3.02 | 0.012872 | 0.0058510 |
| S19-04 | | 1/8 | 720 | 1590 | 4.49 | 3.02 | 0.012872 | 0.0058510 |
| S19-M04 | 4 | 5/32 | 1280 | 2820 | 7.81 | 5.25 | 0.007378 | 0.0033537 |
| S19-06 | | 3/16 | 1800 | 3970 | 10.6 | 7.12 | 0.005080 | 0.0023091 |
| S19-M05 | 5 | | 2000 | 4400 | 12.2 | 8.20 | 0.004627 | 0.0021032 |
| S19-07 | | 7/32 | 2470 | 5440 | 15.1 | 10.1 | 0.003744 | 0.0017018 |
| S19-M06 | 6 | | 2880 | 6350 | 17.6 | 11.8 | 0.003224 | 0.0014655 |
| S19-08 | | 1/4 | 3220 | 7100 | 19.4 | 13.0 | 0.002873 | 0.0013059 |
| S19-M07 | 7 | 9/32 | 3550 | 7800 | 23.9 | 16.1 | 0.002274 | 0.0010336 |
| S19-M08 | 8 | 5/16 | 4640 | 10300 | 31.2 | 21.0 | 0.001833 | 0.0008332 |
| S19-12 | | 3/8 | 6580 | 14500 | 43.2 | 29.0 | 0.001277 | 0.0005805 |
| S19-M10 | 10 | | 7250 | 16000 | 48.8 | 32.8 | 0.001157 | 0.0005259 |
| S19-M11 | 11 | 7/16 | 8770 | 19340 | 59.1 | 39.7 | 0.000936 | 0.0004255 |
| S19-M12 | 12 | | 10400 | 22930 | 70.3 | 47.2 | 0.000806 | 0.0003664 |
| S19-16 | | 1/2 | 11650 | 25680 | 79.3 | 53.3 | 0.000718 | 0.0003264 |
| S19-M14 | 14 | 9/16 | 14180 | 31260 | 95.7 | 64.3 | 0.000566 | 0.0002573 |
| S19-M16 | 16 | 5/8 | 18560 | 40920 | 125 | 84.0 | 0.000460 | 0.0002091 |
| S19-M19 | 19 | 3/4 | 21620 | 47660 | 176 | 118 | 0.000319 | 0.0001450 |
| S19-M22 | 22 | 7/8 | 29070 | 64090 | 236 | 159 | 0.000235 | 0.0001068 |
| S19-M26 | 26 | 1 | 40600 | 89500 | 330 | 222 | 0.000180 | 0.0000818 |
| S19-M28 | 28 | 1 1/8 | 52600 | 115960 | 383 | 257 | 0.000142 | 0.0000645 |
| S19-M30 | 30 | 1 3/16 | 58800 | 129600 | 443 | 298 | 0.000127 | 0.0000577 |
| S19-M32 | 32 | 1 1/4 | 62800 | 138450 | 500 | 336 | 0.000115 | 0.0000523 |