

1 X 19 Stainless Steel Wire - Standing Rigging



1 X 19

Part Number	Nominal Diameter		Minimum Breaking Load		Approximate Weight		Stretch	
	mm	in	kg	lb	kg/100m	lb/100ft	mm/mm/1000kg	in/in/1000lb
S19-M02	2		320	705	1.95	1.31	0.028961	0.0131642
S19-M025	2.5	3/32	500	1100	3.05	2.05	0.018535	0.0084251
S19-M03	3		720	1590	4.49	3.02	0.012872	0.0058510
S19-04		1/8	720	1590	4.49	3.02	0.012872	0.0058510
S19-M04	4	5/32	1280	2820	7.81	5.25	0.007378	0.0033537
S19-06		3/16	1800	3970	10.6	7.12	0.005080	0.0023091
S19-M05	5		2000	4400	12.2	8.20	0.004627	0.0021032
S19-07		7/32	2470	5440	15.1	10.1	0.003744	0.0017018
S19-M06	6		2880	6350	17.6	11.8	0.003224	0.0014655
S19-08		1/4	3220	7100	19.4	13.0	0.002873	0.0013059
S19-M07	7	9/32	3550	7800	23.9	16.1	0.002274	0.0010336
S19-M08	8	5/16	4640	10300	31.2	21.0	0.001833	0.0008332
S19-12		3/8	6580	14500	43.2	29.0	0.001277	0.0005805
S19-M10	10		7250	16000	48.8	32.8	0.001157	0.0005259
S19-M11	11	7/16	8770	19340	59.1	39.7	0.000936	0.0004255
S19-M12	12		10400	22930	70.3	47.2	0.000806	0.0003664
S19-16		1/2	11650	25680	79.3	53.3	0.000718	0.0003264
S19-M14	14	9/16	14180	31260	95.7	64.3	0.000566	0.0002573
S19-M16	16	5/8	18560	40920	125	84.0	0.000460	0.0002091
S19-M19	19	3/4	21620	47660	176	118	0.000319	0.0001450
S19-M22	22	7/8	29070	64090	236	159	0.000235	0.0001068
S19-M26	26	1	40600	89500	330	222	0.000180	0.0000818
S19-M28	28	1 1/8	52600	115960	383	257	0.000142	0.0000645
S19-M30	30	1 3/16	58800	129600	443	298	0.000127	0.0000577
S19-M32	32	1 1/4	62800	138450	500	336	0.000115	0.0000523