

7 X 19 Stainless Steel Wire - Running Rigging



7 X 19

Part Number	Nominal Diameter		Minimum Breaking Load		Approximate Weight		Stretch	
	mm	in	kg	lb	kg/100m	lb/100ft	mm/mm/1000kg	in/in/1000lb
S719-M02	2		226	498	1.53	1.03	0.065672	0.0298511
S719-003	2.5	3/32	355	783	2.38	1.60	0.042030	0.0191047
S719-M03	3		510	1120	3.34	2.24	0.029188	0.0132671
S719-004		1/8	510	1120	3.34	2.24	0.026059	0.0118449
S719-M04	4	5/32	907	2000	5.94	3.99	0.016418	0.0074628
S719-006		3/16	1280	2820	8.41	5.65	0.011582	0.0052644
S719-M05	5		1420	3130	9.29	6.24	0.010508	0.0047762
S719-007		7/32	1750	3860	11.50	7.73	0.008509	0.0038677
S719-M06	6		2040	4500	13.40	9.00	0.007297	0.0033168
S719-008		1/4	2290	5050	15.00	10.08	0.006515	0.0029612
S719-M07	7	9/32	2780	6130	18.20	12.23	0.005361	0.0024368
S719-M08	8	5/16	3630	8000	23.80	15.99	0.004105	0.0018657
S719-012		3/8	5150	11300	33.70	22.65	0.002895	0.0013161
S719-M10	10		5670	12500	37.20	25.00	0.002627	0.0011940
S719-M12	12		8160	18000	53.50	35.95	0.001824	0.0008292
S719-016		1/2	9150	20200	59.90	40.25	0.001629	0.0007403
S719-M14	14	9/16	11100	24500	72.80	48.92	0.001340	0.0006092
S719-M16	16	5/8	13600	30000	99.00	66.52	0.001026	0.0004664