

## Dyform Stainless Steel Wire - Standing Rigging



Dyform

Part Number	Nominal Diameter	Construction	Minimum Breaking Load		Approximate Weight		Stretch	
	mm		kg	lb	kg/100m	lbs/100ft	mm/mm/1000kg	in/in/1000lb
SD07-M025	2.5	1 x 7	690	1521	3.40	2.28	0.014523	0.0066014
SD07-M03	3	1 x 7	1000	2205	4.90	3.29	0.010085	0.0045841
SD07-M035	3.5	1 x 7	1350	2976	6.70	4.50	0.007410	0.0033682
SD07-M04	4	1 x 7	1780	3924	8.80	5.91	0.005673	0.0025787
SD19-M05	5	1 x 19	2440	5379	13.50	9.07	0.003728	0.0016946
SD19-M06	6	1 x 19	3550	7826	19.40	13.04	0.002589	0.0011768
SD19-M07	7	1 x 19	4910	10825	26.00	17.47	0.001902	0.0008646
SD19-M08	8	1 x 19	6150	13558	34.50	23.18	0.001456	0.0006618
SD19-M10	10	1 x 19	9770	21539	54.00	36.29	0.000932	0.0004236
SD19-M12	12	1 x 19	14400	31747	80.70	54.23	0.000647	0.0002941
SD25-M14	14	1 x 25	19300	42549	115.00	77.28	0.000476	0.0002164
SD25-M16	16	1 x 25	25600	56438	147.00	98.78	0.000364	0.0001655
SD31-M19	19	1 x 31	32000	70548	207.00	139.10	0.000258	0.0001173